

Improved Animal Faeces Collector Device

The present invention relates to an improved device for catching and containing animal faeces, particularly dog
5 faeces.

International Publication No. WO 96/07317 (in the name of inventor John Charles Mark LANGLEY and assigned to the applicant for the present invention) discloses a dog faeces
10 collector which has significant practical and economic advantages over previously known dog faeces collectors. The device disclosed in WO 96/07317 describes a device having a collapsible elongate handle provided at a distal end with a receptacle having an upwardly facing deposition surface
15 which, in a deployed condition, is formed and arranged for receiving a faecal deposit. The elongate handle is formed and arranged so as to be collapsible into a highly compact pocketable form in a collapsed state of the device and can be deployed to a substantially self-supporting state in a
20 deployed empty state of the device. In particular the invention is based upon the recognition, for the first time, that the handle and receptacle support means may have a load bearing capability just sufficient for bearing, in cantilevered support, an empty receptacle and which is
25 substantially insufficient for bearing, in cantilevered support, the turning moment exerted by the faecally loaded

receptacle. In a preferred embodiment described in WO 96/07317 the handle and receptacle support means are inflatable.

5 WO 96/07317 describes the use of a "security means" in the form of a closure means such as a cover or, preferably, a draw string or like means for drawing in together the rim or support means of the receptacle over the contents (faeces) of the receptacle. In the specific embodiment described therein
10 the draw string passes down through the handle and around the inflated receptacle support such that when the draw string is pulled the rim portion for supporting the receptacle "draws the centre portion 12 of the tube 2 together so as to cover over the contents 32 of the bag 14 sealing them inside so
15 that a user may safely and hygienically dispose of the device 1 and the contents contained therein".

What the inventor of the present invention has identified is that whilst the arrangement described above and in WO
20 96/07317 functions perfectly well, from a manufacturing and economic point of view use of an additional component part, in the form of a drawstring, is less than desirable.

It is an object of the present invention to avoid or minimise
25 one or more of the foregoing limitations.

-3-

The present invention provides an animal faeces collector device comprising a collapsible elongate handle means provided at a distal end with a receptacle support means supporting a receptacle having an upwardly facing deposition surface in a deployed condition of the device for receiving a faecal deposit thereon, said elongate handle means and said receptacle support means being formed and arranged for supporting the receptacle in empty and faecally loaded conditions thereof, and said elongate handle means, said receptacle support means and said receptacle being formed and arranged so as to be collapsible into a highly compact pocketable form in a collapsed state of the device, and to be deployable to a substantially self supporting state in a deployed empty state of the device, said device being of lightweight form of construction with said handle means and said receptacle support means formed and arranged so as to have a load bearing capability, at least in use of the device, which is just sufficient for bearing, in cantilevered support, the turning moment exerted by said handle means and said receptacle in an empty condition for enabling substantially positive remote manipulation of said empty receptacle into a faeces-receiving position on the ground substantially below an animal's anus in use of the device; said handle means and receptacle support means being formed and arranged with a tensile strength and substantially restricted rigidity and a lightness of construction, to

maximise collapsibility into a highly compact pocketable form and to facilitate easy and economic disposability of the device, and which load bearing capability is substantially insufficient for bearing, in cantilevered support, the

5 turning moment exerted by the receptacle in a faecally loaded condition thereof; whilst enabling the receptacle to be captively suspended in a faecally loaded condition thereof by said handle means for conveyance of the faecally loaded device to a disposal site, in use of the device,

10 characterised in that in said deployed condition of the device said receptacle is supported substantially equally around the receptacle support means by a rim portion and that said rim portion of said receptacle may move on said receptacle support means from a first position with said

15 deposition surface of said receptacle in said upwardly facing orientation to a second position on a portion of said receptacle support means with said deposition surface loaded with faeces and the rim portion of said receptacle collected together over the contents of the receptacle.

20

Thus with the animal faeces collector device according to the present invention the weight of faeces contained within the receptacle causes the rim portion of the receptacle to slide down on the receptacle support means when the device is

25 suspended in a faecally loaded condition.

-5-

Preferably said device is formed and arranged so as to be inflatable from said collapsed state to said substantially self-supporting state. For example, the elongate handle portion may comprise a single elongate inflatable tube, or a
5 plurality of elongate inflatable tubes, in side by side relation.

Desirably said receptacle is supported equally around the receptacle support means by said rim portion such that it may move from said first position to said second position in an
10 inflated, deflated or partially deflated condition of the device.

Preferably said elongate handle portion and said receptacle support means are inflatable and are in fluid communication
15 with each other so as to permit inflation of both the handle portion and the receptacle support means by one use of one inflation means. The inflation means may comprise, for example, the user blowing into a mouthpiece located at the top end of the handle, remote from the receptacle support.

20

Preferably the receptacle is provided with a foot engagement portion, for engaging with the underside of a user's foot so as to allow the raising of the handle and the receptacle support means up from the ground (whilst retaining the
25 receptacle substantially on the ground) so that the receptacle slides from said first position where it is

-6-

supported equally around the receptacle support means to said second position wherein the rim portion of the receptacle collects together over the contents of receptacle and is supported on only a portion of said receptacle support means
5 (which may be in an inflated, deflated or partially deflated state).

Preferably there is used in the construction of the inflatable device, a light, flexible, waterproof material
10 such as plastic sheet material for instance polyvinylchloride, polyamide, polyalkene, polyethylene. Desirably there is used a biodegradable material to facilitate environmentally acceptable disposal of the closed receptacle with the faecal matter contained therein.

15

Preferably said deposition surface when in said deployed condition has a diameter of from 5 cm to 30 cm, desirably 10 cm to 20 cm, though it will be appreciated that the size and shape required will depend to a large extent on the size of
20 the dog and of the faecal deposits generally produced by such a dog. Various shapes of deposition surface may be used, for example, circular, oval, triangular or sectoral. It will be appreciated that the shape of the deposition surface will be dictated substantially by the shape of the receptacle support
25 means.

Further preferred features and advantages of the present invention will appear from the following detailed description given by way of example of a preferred embodiment illustrated with reference to the accompanying drawings in which: -

- 5 Fig. 1 is a perspective view of a dog faeces collector device in an inflated self supporting state; and
Fig. 2 is a perspective view of the device after use in a collapsed condition
- 10 Reference is first made to Fig. 1 and Fig. 1a which shows a dog faeces collector device of the invention generally indicated by reference number 1. In more detail the device 1 comprises a collapsible elongate handle 2 provided at a distal end 4 with a receptacle support ring 6 (shown
- 15 partially in dashed line) for supporting a receptacle 8 having an upwardly facing deposition surface 10. The handle 2 and the receptacle support ring are formed from two inflatable tubes. In the inflated condition shown in Fig. 1 the receptacle 8 is supported on the receptacle support ring
- 20 6 by a rim portion 12. In more detail the rim portion 12 of the receptacle 8 comprises an elongate tube 14 which runs around the top of the receptacle 8 and through which said receptacle support ring 6 passes. The rim portion 12 is not fixed to the receptacle support ring 6 but may move slidably
- 25 thereon (likened to a curtain on a curtain rail). In the inflated condition shown in Fig. 1 the receptacle 8 is

supported equally around the receptacle support ring 6 by the rim portion 12 so as to define the deposition surface 10 on the receptacle 8.

- 5 The handle 2 and receptacle support ring 6 comprise two inflatable tubes which are inflated through a mouthpiece 16 at the top 18 of the handle 2. The handle 2 itself comprises two side by side tubes (indicated by a dashed line) which at the distal end 4 of the handle 2 split to form the receptacle support ring 6. The ends of both tubes are connected together 20.

- Also shown in Fig. 1 is a foot engagement strap 22 which is attached to the receptacle 8. The foot engagement strap 22 provides a means for holding the receptacle 8 down whilst the handle 2 is pulled upwardly thereby causing the receptacle support ring 6 to be partially withdrawn from within the rim portion 12 of the receptacle 8 and thereby causing the rim portion 12 to collect together and slide down (shown by arrows A in Fig. 2) over the receptacle support ring 6 towards the portion 20 where the two inflatable tubes of the receptacle support ring 6 are joined. The receptacle 8 is then captively held by the end of the support ring 6.

- 25 Fig. 2 shows the device of Fig. 1 with faeces 24 contained within the receptacle 8 and the rim portion 12 of the

receptacle 8 collected in on itself (like an open curtain) covering over the contents and being supported at the end of the receptacle support ring 6 (which may be in an inflated, partially inflated or deflated condition).

5

Various modifications may be made to the above-described embodiment without departing from the scope of the present invention.

10

-10-
CLAIMS

1. An animal faeces collector device ~~(1)~~ comprising a collapsible elongate handle means (2) provided at a distal
5 (4) end with a receptacle support means (6) supporting a receptacle (8) having an upwardly facing deposition surface (10) in a deployed condition of the device for receiving a faecal deposit (24) thereon, said elongate handle means (2) and said receptacle support means (6) being formed and
10 arranged for supporting the receptacle (8) in empty and faecally loaded conditions thereof, and said elongate handle means (2), said receptacle support means (6) and said receptacle (8) being formed and arranged so as to be collapsible into a highly compact pocketable form in a
15 collapsed state of the device, and to be deployable to a substantially self supporting state in a deployed empty state of the device, said device being of lightweight form of construction with said handle means (2) and said receptacle support means (6) formed and arranged so as to have a load
20 bearing capability, at least in use of the device, which is just sufficient for bearing, in cantilevered support, the turning moment exerted by said handle means (2) and said receptacle (8) in an empty condition for enabling substantially positive remote manipulation of said empty
25 receptacle (8) into a faeces-receiving position on the ground substantially below an animal's anus in use of the device;

-11-

said handle means (2) and receptacle support means (6) being formed and arranged with a tensile strength and substantially restricted rigidity and a lightness of construction, to maximise collapsibility into a highly compact pocketable form and to facilitate easy and economic disposability of the device, and which load bearing capability is substantially insufficient for bearing, in cantilevered support, the turning moment exerted by the receptacle (8) in a faecally loaded condition thereof; whilst enabling the receptacle (8) to be captively suspended in a faecally loaded condition thereof by said handle means (2) for conveyance of the faecally loaded device to a disposal site, in use of the device, characterised in that in said deployed condition of the device said receptacle (8) is supported substantially equally around the receptacle support means (6) by a rim portion (12) and that said rim portion (12) of said receptacle (8) may move on said receptacle support means (6) from a first position with said deposition surface (10) of said receptacle (8) in said upwardly facing orientation to a second position on a portion of said receptacle support means (6) with said deposition surface (10) loaded with faeces (24) and the rim portion of said receptacle (12) collected together over the contents of the receptacle (8).

2. An animal faeces collector device as claimed in claim 1 wherein said device (1) is formed and arranged so as to be

inflatable from said collapsed state to said substantially self-supporting state.

3. An animal faeces collector device (1) as claimed in claim 1 or claim 2 wherein said elongate handle portion (2) and said receptacle support means (6) are inflatable and are in fluid communication with each other.

4. An animal faeces collector device (1) as claimed in any one of claims 1 to 3 wherein the receptacle (8) is provided with a foot engagement portion (22), formed and arranged for engaging, in use, with the underside of a user's foot so as to allow the raising of the handle (2) and the receptacle support means (6) up from the ground.

15

5. An animal faeces collector device (1) as claimed in any one of claims 2 to 4 wherein the material used in the construction of the inflatable device is of a light, flexible, waterproof plastic sheet material selected from the group including polyvinylchloride, polyamide, polyalkene or polyethylene.

6. An animal faeces collector device (1) as claimed in any one of claims 2 to 4 wherein the material used in the construction of the inflatable device is biodegradable.

25

7. An animal faeces collector device (1) as claimed in any one of claims 1 to 6 wherein said deposition surface (10) when in said deployed condition has a diameter of from 5 cm to 30 cm.

5

8. An animal faeces collector device (1) as claimed in any one of claims 1 to 6 wherein said deposition surface (10), when in said deployed condition has a diameter of from 10 to 20 cm.

10

9. An animal faeces collector device (1) as claimed in any one of claims 1 to 8 wherein said handle (2) and receptacle support means (6) comprises two inflatable tubes inflatable through a mouthpiece (16) at the top end (18) of said handle.

15




Fig. 1




Fig. 2




Fig. 1a

INTERNATIONAL SEARCH REPORT

national Application No

PCT/GB2004/002734

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A01K23/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 A01K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 96/07317 A (LANGLEY JOHN CHARLES MARK) 14 March 1996 (1996-03-14) cited in the application page 2, lines 16-36 page 5, lines 6-10, 19-21 page 7, lines 23-26 page 8, lines 16-22, 30-65 page 10, lines 5-8 figure 2	1-3, 5, 7-9
A	US 4 185 861 A (BERNER CHARLES R) 29 January 1980 (1980-01-29) column 2, lines 36-40, 57-61 column 3, lines 38-40 figure 4	1

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

S document member of the same patent family

Date of the actual completion of the international search

24 September 2004

Date of mailing of the international search report

05/10/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Been, M

INTERNATIONAL SEARCH REPORT

Information on patent family members

national Application No

T/GB2004/002734

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9607317	A	14-03-1996	AT 185470 T	15-10-1999
			AU 699843 B2	17-12-1998
			AU 3352295 A	27-03-1996
			CA 2198627 A1	14-03-1996
			DE 69512795 D1	18-11-1999
			DE 69512795 T2	06-07-2000
			DK 778729 T3	17-04-2000
			EP 0778729 A1	18-06-1997
			ES 2141375 T3	16-03-2000
			FI 970909 A	03-03-1997
			WO 9607317 A1	14-03-1996
			GB 2305355 A ,B	09-04-1997
			GR 3032322 T3	27-04-2000
			JP 10505240 T	26-05-1998
			NO 970937 A	15-04-1997
			NZ 291874 A	29-04-1999
			PT 778729 T	28-04-2000
			US 5758917 A	02-06-1998
US 4185861	A	29-01-1980	NONE	